

10/23/00  
1c955 U.S. PTO

10/24/00

A

# LERNER AND GREENBERG, P.A.

PATENT ATTORNEYS AND ATTORNEYS AT LAW

2445 Hollywood Boulevard  
Hollywood, Florida 33020  
Tel: (954) 925-1100  
Fax: (954) 925-1101

Herbert L. Lerner (NY Bar)  
Laurence A. Greenberg (FL Bar)

Werner H. Stemer (FL Bar), Senior Attorney

Ralph E. Locher (FL, IL, MO Bars)  
Manfred Beck (US & German Pat. Agent)  
Mark P. Weichselbaum (TN Bar)  
Gregory L. Mayback (FL Bar)  
Markus Nollf (FL Bar)  
Otto S. Kauder (Reg. Pat. Agent)  
Loren Donald Pearson (FL Bar)

PATENTUSA<sup>SM</sup>  
www.patentusa.com  
patents@patentusa.com

Mailing Address:  
Post Office Box 2480  
Hollywood, FL 33022-2480

New York Office  
153 E 57th Street  
Suite 15G  
New York, NY 10022

jc922 U.S. PTO  
09/694570

10/23/00

"Express Mail" mailing label number EL608557895US

Date of Deposit October 23, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Docket No.: E-41119

  
MICHAEL BURNS

Date: October 23, 2000

Hon. Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Enclosed herewith are the necessary papers for filing the following application for Letters Patent:

Applicant : LUDWIG WIERES ET AL.

Title : METHOD AND DEVICE FOR PRODUCING A METALLIC  
HONEYCOMB BODY

2 sheets of informal drawings in triplicate.

A check in the amount of \$ 710.00 covering the filing fee.

Claim for Priority. Certified copy of the corresponding foreign patent application No.

198 17 787.9 filed April 21, 1998.

Information Disclosure Statement and 6 References.

PCT Publication (cover sheet only).

This application is being filed without a signed oath or declaration under the provisions of 37 CFR 1.53(d). Applicants await notification of the date by which the oath or declaration and the surcharge are due, pursuant to this rule.

The Patent and Trademark Office is hereby given authority to charge Deposit Account No. 12-1099 of Lerner and Greenberg, P.A. for any fees due or deficiencies of payments made for any purpose during the pendency of the above-identified application.

Respectfully submitted,



For Applicants  
LAG:kc

WERNER H. STEMER  
REG. NO. 34,956

METHOD AND DEVICE FOR PRODUCING A METALLIC  
HONEYCOMB BODY

5

Cross-Reference to Related Application:

This is a continuation of copending International Application PCT/EP99/02585, filed April 16, 1999, which designated the United States.

10

Background of the Invention:

Field of the Invention:

The subject of the invention relates to a method for producing a metallic honeycomb body and to a device for producing a metallic honeycomb body.

15

For the reduction of pollutants in exhaust gases, in particular in motor vehicle exhaust gases, so-called catalysts are used. The catalysts contain a carrier body which is provided with a catalytically active coating. The carrier body has a multiplicity of ducts through which an exhaust gas is capable of flowing. It has a honeycombed structure, and therefore such carrier bodies are designated as honeycomb bodies.

20

25

It is known that such a honeycomb body may be a monolithic body that is produced, for example, from a ceramic material. Honeycomb bodies are also known which contain a metallic material. Such honeycomb bodies may be produced, for example, by sintering or casting. Metallic honeycomb bodies that contain at least partially structured sheet metal layers are also known.

European Patent EP 0 263 324 B1 describes a metallic honeycomb body which is formed from a corrugated or a smooth and a corrugated metal strip. The metal strip or metal strips are wound or folded to form a plurality of layers contiguous to one another. European Patent EP 0 263 324 B1 shows a spirally wound honeycomb body. The spirally wound honeycomb body is introduced into a casing tube with the aid of an introduction unit.

International Patent Disclosure WO 97/06358 discloses a method for producing a honeycomb body having a multiplicity of ducts permeable to a fluid, from a multiplicity of at least partially structured metal sheets. According to this method, a stack composed of a plurality of at least partially structured metal sheets is disposed in layers. The stack is introduced into an open mold and is held in the latter in a central region by a holding device. At least two mold segments of the mold are in each case displaced out of their

initial positions in such a way that at least a portion of each casing section comes to bear on the stack and is subsequently moved along a path of movement corresponding to the outer shape until a predetermined degree of wrap is achieved. The mold is then closed. The matrix thus produced is introduced into a casing tube.

International Patent Disclosure WO 97/06358 describes, furthermore, a method in which a plurality of stacks composed of a plurality of at least partially structured metal sheets are disposed in layers. Each stack is folded in each case about a bending line. The stacks are introduced into an open mold and are held in the latter in a central region by a holding device. At least two mold segments are in each case displaced out of their initial positions in such a way that at least a portion of each casing section comes to bear on the stack and is subsequently moved along a path of movement corresponding to the outer shape until a predetermined degree of wrap is achieved. The mold is then closed. The matrix thus produced is introduced into a casing tube.

International Patent Disclosure WO 97/00135 discloses further methods for producing a honeycomb body, having a multiplicity of ducts permeable to a fluid, from a multiplicity of at least partially structured sheet metal layers. In these methods too, a matrix composed of at least one at least partially

structured sheet metal layer, which is wound, layered or wrapped, is formed. The matrix is introduced into a casing tube.

5 While the matrix is being produced, stresses distributed unevenly over the cross section of the matrix occur and may lead to defects and to dimensional inaccuracies after a soldering operation that follows the production of the honeycomb body. This problem arises to an increased extent  
10 when the matrix is formed from sheet metal layers that have a microstructure and a macrostructure, in particular a transverse microstructure.

#### Summary of the Invention:

15 It is accordingly an object of the invention to provide a method and a device for producing a metallic honeycomb body that overcomes the above-mentioned disadvantages of the prior art methods and devices of this general type, in which an equalization of the stresses over the cross section of a  
20 matrix is obtained.

With the foregoing and other objects in view there is provided, in accordance with the invention, a method for producing a metallic honeycomb body. The method includes the  
25 steps of providing a matrix formed of at least one at least partially structured sheet metal layer being one of wound,

layered and wrapped to form the matrix; vibrating the matrix by an external excitation; and introducing the matrix into a casing tube.

- 5 In the method according to the invention, the matrix is wound, layered or wrapped from at least one at least partially structured sheet metal layer. The matrix is set in vibration by the external or independent excitation and is introduced into the casing tube during the excitation or after the
- 10 excitation. Since the matrix is set in vibration by the excitation, an equalization of the stresses in the cross section of the matrix is achieved. This equalization also leads to possible gaps between adjacent sheet metal layers being closed, since, due to the independent excitation of the
- 15 matrix, an essentially homogeneous relief of stress of the matrix occurs. A more even stress distribution also leads, in the case of a matrix containing smooth and structured sheet metal layers, to the contact forces at the contact points between the smooth and the structured sheet metal layers being
- 20 distributed more homogeneously, with the result that an improved diffusion connection can be achieved between the sheet metal layers or between the matrix and the casing tube.

It became clear, in particular, that, in the method according to the invention, a more homogeneous stress distribution over

25 the cross section of the matrix can be achieved in the matrix

that is formed by sheet metal layers with a microstructure and a macrostructure.

The excitation of the matrix may take place periodically, in a pulse-like manner or randomly in time. It is particularly expedient if the matrix is set in vibration by periodic excitation.

According to a further advantageous refinement of the method, it is proposed that the matrix be set in vibration by kinematic excitation. The advantage of this is that the excitation can be carried out at relatively low outlay. In particular, a kinematic excitation of the matrix has the advantage that relatively low sound emission due to the kinematic excitation occurs.

Alternatively or additionally to a kinematic excitation of the matrix, it is proposed that the matrix be set in vibration by the action of force. The advantage of external excitation by the action of force is that the excitation can be achieved by a relatively high frequency. Furthermore, a predetermined energy can be introduced into the matrix by the action of force.

According to a further advantageous refinement of the method, it is proposed that the matrix be introduced into the casing

tube by the introduction or guide unit, the matrix being compressed and set in vibration during the leadthrough operation. The advantage of this procedure is that the forces necessary for introducing the matrix into the casing tube are reduced. This also results in a reduction in the deformation of the matrix in an end face on which engages a transport element pushing the matrix into the casing tube. This also leads to an improvement in the quality of the honeycomb body.

10 The excitation of the matrix preferably takes place in such a way that the matrix is set in transverse vibration by the excitation.

15 According to a further idea of the invention, a device is proposed for producing a metallic honeycomb body which has at least one matrix which is wound, layered or wrapped from at least one at least partially structured sheet metal layer and which is disposed in the casing tube. The device is distinguished by a introduction unit which has an entry  
20 orifice and an exit orifice and also a guide duct narrowing from the entry orifice toward the exit orifice. A transport element is capable of being moved in the duct and out of it, the transport element pushing a matrix through the entry orifice into the duct and pressing it via the exit orifice out  
25 of the guide unit into a casing tube. The device according to the invention has an exciting unit that is connected to the



guide unit and by which the guide unit is set in vibration.

The guide unit is set in vibration, in particular,

transversely to the axial direction of the duct. When a

matrix is located in the guide unit, the matrix is set in

5 vibration via the guide unit, with the result that an essentially homogeneous relief of stress of the matrix is achieved in the guide unit.

10 To simplify the introduction of the matrix into a casing tube and for positioning the casing tube exactly in relation to the duct, it is proposed that the exit orifice be followed by a positioning unit, by which the casing tube can be positioned essentially coaxially to the duct.

15 According to a further advantageous refinement of the device, it is proposed that the entry orifice be preceded by a centering unit, so that it becomes simpler for the matrix to be introduced into the duct of the guide unit.

20 According to a further advantageous refinement of the device, it is proposed that the introduction or guide unit be mounted elastically. An active insulation of the guide unit is achieved by the elastic mounting of the guide unit. By virtue of the active insulation of the vibration unit, no or only  
25 very slight vibrational forces pass into the surroundings.

External concussions do not reach the guide unit, or only to a

very slight extent, so that passive insulation is also afforded.

According to a further advantageous refinement of the device,  
5 it is proposed that the exciting unit introduce an oscillating force into the guide unit, the force running essentially transversely to the longitudinal direction of the duct. Alternatively or additionally, the exciting unit may set the guide unit kinematically in vibration transversely to the  
10 longitudinal direction of the duct.

Other features which are considered as characteristic for the invention are set forth in the appended claims.

15 Although the invention is illustrated and described herein as embodied in a method and a device for producing a metallic honeycomb body, it is nevertheless not intended to be limited to the details shown, since various modifications and structural changes may be made therein without departing from  
20 the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention, however, together with additional objects and advantages  
25 thereof will be best understood from the following description

of specific embodiments when read in connection with the accompanying drawings.

Brief Description of the Drawings:

5 Fig. 1 is a diagrammatic, sectional view of a first exemplary embodiment of a device for producing a metallic honeycomb body according to the invention; and

10 Fig. 2 is a diagrammatic, sectional view of a second exemplary embodiment of the device for producing the metallic honeycomb body.

Description of the Preferred Embodiments:

15 In all the figures of the drawing, sub-features and integral parts that correspond to one another bear the same reference symbol in each case. Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is shown a matrix 1 which is wound, layered or wrapped from at least one at least partially structured sheet metal  
20 layer. The matrix 1 may be produced by one of the methods described in International Patent Disclosure WO 97/00135, International Patent Disclosure WO 97/06358 or European Patent EP 0 263 324 B1. Other methods are also possible. The matrix  
25 1 has ducts, through which an exhaust gas is capable of flowing and which are delimited by the wound, layered or wrapped sheet metal layers.

The device has an introduction unit 3. The introduction unit has an entry orifice 4 and an exit orifice 5. The entry orifice 4 and the exit orifice 5 are connected to one another by a guide duct 6. The guide duct 6 narrows in cross section from the entry orifice 4 toward the exit orifice 5.

10 The introduction unit 3 is preceded by a centering unit 10 having a centering duct 11 that narrows toward the entry orifice 4.

The introduction unit 3 is followed by a positioning unit 12. The positioning unit 12 has a positioning slope 13. The positioning unit 12 is of an annular configuration. A free end region of a casing tube 2 engages into the introduction slope 13. The casing tube 2 is oriented essentially coaxially to an axis 19 of the guide duct 6 by the positioning slope 13.

20 The introduction unit 3 is mounted elastically. The elastic mounting of the introduction unit 3 is not illustrated in the exemplary embodiment shown. The elastic mounting may, for example, contain elastomeric elements or air cushions, on which the introduction unit 3 is mounted.

25 An exciting unit 14 is connected to the introduction unit 3. The exciting unit 14 contains a disk 15 that is connected to a

non-illustrated drive unit. The disk 15 is connected to the introduction unit 3 via a rod 16. The connection of the rod 16 to the introduction unit 3 is articulated at 17. The connection of the rod 16 to the disc 15 is also articulated at 18. The disk 15 is capable of being set in rotational movement according to the arrow illustrated in Fig. 1. The rotational movement of the disk 15 is converted into a translational movement of the introduction unit 3 by the rod 16 and the articulated connections 17, 18, so that the introduction unit 3 is set in vibration about the axis 19.

The amplitude of the vibration transversely to the axis 19 is not so great that the matrix 1 is subjected to shearing stress when it is led through the centering unit 10 into the introduction unit 3 or out of the introduction unit 3 into the positioning unit 12. The matrix 1 is pushed into the introduction unit 3 along the axis 19 via the centering unit 10. The matrix 1 is pushed out of the introduction unit 3 into the casing tube 2 via the positioning unit 12. A transport element 7 is provided for moving the matrix 1. The transport element 7 has a ramhead 8 that is connected to an actuating rod 9. The ramhead 8 presses against an end face of the matrix 1, so that the matrix 1 can be moved toward the casing tube 2. After the matrix 1 has been introduced into the casing tube 2, the transport element 7 is moved back into its initial position, so that the latter is ready for

introducing a further matrix 1 into a further casing tube 2,  
which have been positioned in the meantime.

The matrix 1 is set in vibration by the exciting unit 14

5 during the transport of the matrix 1 in the introductory unit  
3 toward the casing tube 2, with the result that the matrix 1  
undergoes an equalization of stresses within the matrix 1, as  
viewed over the cross section.

10 Since the vibrations take place transversely to the direction  
of movement of the matrix 1 and therefore also to the  
transport element 7, the force required for introducing the  
matrix 1 into the casing tube 2 is lowered.

15 Fig. 2 shows a second exemplary embodiment of the device for  
producing the metallic honeycomb body. The device contains  
the introduction unit 3 that has the entry orifice 4 and the  
exit orifice 5. The entry orifice 4 is connected to the exit  
orifice 5 via the guide duct 6. The guide duct 6 narrows  
20 toward the exit orifice 5. The guide duct 6 is essentially of  
a conical shape in cross section.

The introduction unit 3 is preceded by the centering unit 10  
which has the centering duct 11. The centering duct 11  
25 likewise has a conical shape.

The introduction unit 3 is followed by the essentially annularly configured positioning unit 12. The positioning unit 12 has, on one end face, the positioning slope 13, into which the end region of the casing tube 2 can be introduced.

- 5 The casing tube 2 can be oriented coaxially to the axis 19 of the guide duct 6 by the positioning slope 13.

The introduction unit 3 is mounted elastically, so that it is uncoupled vibrationally from the surroundings. The

- 10 introduction unit 3 can be set in vibration by an exciting unit 20. The exciting unit 20 contains a drive unit 21 and a tappet 22. The tappet 22 is capable of being moved back and forth essentially transversely to the axis 19. A free end of the tappet 22 conducts a force in a pulse-like manner into the  
15 introduction unit 3, with the result that the latter and also the matrix 1 located in the introduction unit 3 are set in vibration.

- The matrix 1 is introduced into the introduction unit 3 and  
20 transported from the latter into the casing tube 2 by the transport element 7. The transport element 7 contains the ramhead 8 that is connected to the actuating rod 9.

We claim:

1. A method for producing a metallic honeycomb body, which comprises the steps of:

providing a matrix formed of at least one at least partially structured sheet metal layer being one of wound, layered and wrapped to form the matrix;

vibrating the matrix by an external excitation; and

introducing the matrix into a casing tube.

2. The method according to claim 1, which comprises vibrating the matrix by an external periodic excitation.

3. The method according to claim 1, which comprises vibrating the matrix by an external kinematic excitation.

4. The method according to claim 1, which comprises vibrating the matrix by an action of force.

5. The method according to claim 1, which comprises using an introduction unit for introducing the matrix into the casing tube, the matrix being compressed and set in vibration during a lead-through operation.



6. The method according to claim 1, which comprises setting the matrix in transverse vibration by the external excitation.

7. The method according to claim 1, which comprises introducing the matrix into the casing tube during a performance of the external excitation.

8. The method according to claim 1, which comprises introducing the matrix into the casing tube after the external excitation is completed.

9. A device for producing a metallic honeycomb body having at least one matrix being one of wound, layered and wrapped from at least one at least partially structured sheet metal layer and disposed in a casing tube, comprising:

an introduction unit having an entry orifice formed therein, an exit orifice formed therein, and a guide duct formed therein and narrowing from said entry orifice toward said exit orifice;

a transport element capable of moving into and out of said guide duct; and

an exciting unit connected to said introduction unit for vibrating said introduction unit.

10. The device according to claim 9, including a positioning unit following said exit orifice and by which the casing tube can be positioned substantially coaxially to said guide duct.

11. The device according to claim 9, including a centering unit preceding said entry orifice.

12. The device according to claim 10, wherein said introduction unit is mounted elastically.

13. The device according to claim 9, wherein said exciting unit introduces an oscillating force into said introduction unit, the oscillating force running substantially transversely to a longitudinal direction of said guide duct.

14. The device according to claim 9, wherein said exciting unit sets the introduction unit kinematically in vibration transversely to a longitudinal direction of said guide duct.

Abstract of the Disclosure:

A method for producing a metallic honeycomb body, according to which at least one at least partly structured metal sheet is coiled, laminated or looped to form a matrix. The matrix is  
5 oscillated by an external excitation and during or after the external excitation is introduced into a casing tube.

REL/kc

FIG. 1 is a cross-sectional view of a device 100 in a closed position. The device 100 includes a housing 10 and a piston 2. The piston 2 is biased by a spring 3. The device 100 is shown in a closed position, with the piston 2 at the top of the housing 10. The device 100 is shown in a cross-sectional view, with the housing 10 and the piston 2 being the main components. The device 100 is shown in a closed position, with the piston 2 at the top of the housing 10. The device 100 is shown in a cross-sectional view, with the housing 10 and the piston 2 being the main components.




Fig. 1




Fig. 2

COMBINED DECLARATION AND POWER OF ATTORNEY  
IN ORIGINAL APPLICATION

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND DEVICE FOR PRODUCING A METALLIC  
HONEYCOMB BODY

described and claimed in the specification bearing that title, that I understand the content of the specification, that I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve month prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application under 37 C.F.R. 1.56a, and that no application for patent or inventor's certificate of this invention has been filed earlier than the following in any country foreign to the United States prior to this application by me or my legal representatives or assigns:

German Application No. 198 17 787.9, filed April 21, 1998, the International Priority of which is claimed under 35 U.S.C. §119; and International Application No. PCT/EP99/02585, filed April 16, 1999, the Priority of which is claimed under 35 U.S.C. §120.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

HERBERT L. LERNER (Reg.No.20,435)  
LAURENCE A. GREENBERG (Reg.No.29,308)  
WERNER H. STEMER (Reg.No.34,956)  
RALPH E. LOCHER (Reg.No. 41,947)

Address all correspondence and telephone calls to:

LERNER AND GREENBERG, P.A.  
POST OFFICE BOX 2480  
HOLLYWOOD, FLORIDA 33022-2480  
Tel: (954) 925-1100  
Fax: (954) 925-1101

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST JOINT INVENTOR: LUDWIG WIERES

INVENTOR'S SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

Residence: OVERATH, GERMANY

Country of Citizenship: GERMANY

Post Office Address: OPPELNER STRASSE 2,  
D-51491 OVERATH  
GERMANY

---

FULL NAME OF SECOND JOINT INVENTOR: HANS-PETER CASPAR

INVENTOR'S SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

Residence: TROISDORF, GERMANY

Country of Citizenship: GERMANY

Post Office Address: LEOSTRASSE 28,  
D-53844 TROISDORF  
GERMANY

---

CHRISTOF MÜLLER

DATE: \_\_\_\_\_

Country of Citizenship: GERMANY

Post Office Address: CHRISTIAN-HEESEN-STRASSE 10,  
D-51491 OVERATH  
GERMANY